

# HOCUT 3380

## Water soluble metalworking fluid

### DESCRIPTION

**HOCUT 3380** is advanced, high lubricity, boron-free emulsion technology giving ultra-long sump-life and enhanced machining performance compared to conventional products.

### APPLICATIONS

**HOCUT 3380** high lubricity characteristics make it recommended for machining difficult materials such as titanium, inconel, and alloy steels.

Low foaming characteristics are specifically designed for modern high-pressure coolant delivery systems. The product is designed primarily for soft water.

Ultra long-life makes the product suitable for both centralised systems and single-sump machines while the advanced boron-free technology extends emulsion life without the need for regular biocide treatments.

Rolls Royce approved

### RECOMMENDATION FOR USE

Medium duty machining 4 - 6%

Heavy duty machining 5 - 10%

Heavy duty grinding 5 - 10%

### TYPICAL PHYSICAL PROPERTIES

Concentrate	Amber oil
Appearance	
Specific Gravity @ 20°C	0.94
Refractometer Factor	1
Emulsion Appearance	Opalescent
pH in Use	8.9-9.8

### BENEFITS

- **High lubricity** : sophisticated package of mineral oil and polar additives extend tool-life
- **Ultra long sump life** : Special '795' technology gives extends intervals between clean outs
- **Very stable emulsion** : fewer additive treatments and lower usage costs
- **Good corrosion protection** : fewer rejects and lower maintenance cost
- **Boron-free** : no SVHC classification under REACH
- **Very low foaming** : ideal for the highest speeds and pressures in soft water
- **Very good EHS profile** : Boron, chlorine and phenol-free. Contains only TRGS611 approved amines

### RELATED PRODUCT

Water soluble coolants are complemented by our full range of high quality, speciality production fluids including energy saving wash chemicals, low misting neat cutting oils, non-VOC rust preventives and long life heat treatment fluids. Fluidcare services complete our value added portfolio with a range of expert services and equipment to help reduce costs and improve productivity. For more information, please contact your local Houghton representative.

### STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

### HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulations (EC) No 1907/2006 Annex II and (EC) No 1272/2008.

RF 2015/07/07 GB



Houghton PLC  
Beacon Road, Trafford Park, Manchester  
M17 1AF, United Kingdom

Tel: +44 (0) 161 874 5000  
Fax: +44 (0) 161 874 5001  
[uk.enquiries@houghtonintl.com](mailto:uk.enquiries@houghtonintl.com)  
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.