

# TECHNICAL DATA SHEET

## RUST VETO® 221 D

### 長效-脫水-防銹油 [ISO 6743-8 REE]

RUST VETO®221 D是脫芳族溶劑和精心挑選的性能添加劑的混合物，可提供長達18個月的室內保護。

RUST VETO® 221 D 是一種優質的防銹脫水劑，並顯示出非常薄的油膜，該膜具有自我修復，抗剝離和抗裂，中和指紋的特性，並且根據需要可以輕鬆去除。

RUSTVETO®221 D對黑色金屬和有色金屬有效，並且不含鉛。

#### 使用方式

RUST VETO®221 D在以下方面提供長期保護和最終保護：  
(半)精加工的汽車和機械零件，例如氣門，齒輪，凸輪軸，箱，軸承，鏈條，電動機，緊固件，制動系統，具有高光潔度的精密零件。

通過填充微孔使表面磷化或變黑。

正確包裝時，在海外運輸期間的材料和設備。

特別耐鹼性研磨冷卻劑，可溶性油乳液和酸性漂洗水氣氛的殘留。

#### 使用建議

有關更多信息，請查閱我們的推薦書和選擇指南。

#### 優勢

- 經濟實用-與大多數潤滑油兼容的高性能薄膜，無需沖洗。
- 經濟實用-分離出的水良好，延長了油槽的使用壽命，減少了槽體的清理頻率。
- 操作員接觸友善-脫芳烴溶劑，無重金屬，如鉛。
- 環保-中等閃點，可限制蒸發和火災風險。
- 品質 -不會破裂或剝落的自修復膜，耐污垢滲透。
- 品質 - 可中和拿取時碰觸時產生的指紋。
- 品質 - 在侵蝕性環境下對鹼性磨削液的殘留具有很高的抵抗力。
- 品質 - 高性能化學物質，可確保您的增值安全並減少返工風險。

#### 健康，安全和處理

請參閱安全數據表 ( SDS )，以獲取有關存儲，安全處理和處置的信息。產品處理，儲存，使用和處置的條件或方法超出了我們的合理控制範圍。

對於因這些條件引起的或與之相關的任何產品無效或任何傷害或損壞，我們不承擔任何責任。

#### 物理性質

屬性	數值	單位
外觀	透明棕色	
比重	0.83	
閃火點	67	ASTM D 93, °C
Viscosity @20°C	4.7	cSt
膜厚	< 5	μm

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet ( SDS ) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 21000221

